

# DECLARATION OF PERFORMANCE

DE0418/02

**PCI**<sup>®</sup>  
Für Bau-Profis

Unique identification code of the product-type:

Augsburg, 24.10.2017

## PCI Elritan<sup>®</sup> 100 (DE0418/02)

Intended use/es:

**EN 15651-1 Type F EXT-INT CC**

**Sealants for non-structural use in joints in buildings and pedestrian walkways**

**Sealants for facade elements, Class 25 LM**

**Conditioning: Method A**

**Substrate: Mortar M1 without primer**

Manufacturer:

**PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg**

System/s of AVCP:

**System 3, System 3 (Reaction to fire)**

Harmonised standard / Notified body/ies:

**EN 15651-1:2012  
GINGER CEBTP (NB 0074)**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	Evaluated	System 3	
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10 %		
Tensile properties at maintained extension after immersion in water at 23 °C	Pass		
Tensile properties at -30 °C	≤ 0,9 MPa		
Tensile properties at maintained extension at -30 °C	Pass		
Durability	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Marc C. Köppe  
managing director



Frank Rösiger  
managing director